



FAIRPRENE® PRODUCT BULLETIN: B8N6

Product Code:

WFP-B8N6T-02556

[Compare to BN-0002* or BN-0047*, Anti-wicking Nitrile on Nylon]



Description:

Engineered Nitrile on medium strength nylon fabric designed to have anti-wicking properties.

Typical Physical Properties:

Polymer	Nitrile (NBR)	
Durometer	60 ±5	ASTM D-2240
Fabric Mullen Burst:	475 psi (min.)	ASTM D-751
Fabric Tensile:	250 x 250 lbf/in.	ASTM D-751
Color:	Black	Visual
Finish Gauge:	.025 ± .004, .050 ± .006	ASTM D-751
Surface Finish:	Smooth, with light talc	Visual
Finished Width:	56" max.	
Non-Wicking:	Properties & test procedures must be agreed to by end user, test to 150 psi. max	

General Polymer Characteristics:

Resistance To:

Aliphatic Hydrocarbons
Aromatic Hydrocarbons
Lacquer Solvents
Oil & Gasoline
Animal & Vegetable Oil
Water Absorption
Oxidation
Ozone
Sunlight
Heat Aging
Flame
Heat
Cold

NBR (Nitrile)

Excellent
Good
Fair
Excellent
Excellent
Fair to Good
Fair to Good
Fair
Fair
Very Good
Fair to Poor
Good to Excellent
Good to Excellent

This data is based on tests believed to be reliable and consistent with industry practices and is presented in good faith. No warranty or representation including but not limited to merchantability or of fitness for use whether expressed or implied is intended or made, nor is protection from law or patent to be inferred. All rights and patents reserved.

Fairprene is a registered trademark of Alpha Engineered Composites.

As always, made 100% in the USA...



*BN-0002 and BN-0047 are used for reference only.