



## FAIRPRENE® PRODUCT BULLETIN: N4N5



**Product Code:**

WFP-N4N5-06048

*[Compare to NN-0060\*, Neoprene on Nylon]*

**Description:**

Special purpose Neoprene elastomer on lightweight nylon base fabric. Suitable for use in diaphragm and gasket applications.

**Typical Physical Properties:**

Base Fabric:	Nylon	2.0 osy
Coating:	Neoprene	
	70 Durometer (Shore A)	ASTM D-412

**Coated Fabric Properties:**

Mullen Burst:	180 psi min.	ASTM D-751
Tensile (Grab):	110 x 110 lbs/in	ASTM D-751
Finish Gauge:	.060" ± .006"	ASTM D-751
Finished Width:	48"	

**General Polymer Characteristics:**

Resistance To:

- Aliphatic Hydrocarbons
- Aromatic Hydrocarbons
- Oxygenated (Ketones, etc.)
- Lacquer Solvents
- Oil & Gasoline
- Animal & Vegetable Oil
- Water Absorption
- Oxidation
- Ozone
- Sunlight
- Heat Aging
- Flame
- Heat
- Cold

**Neoprene (CR)**

- Good
- Fair
- Poor
- Poor
- Good
- Good
- Good to Excellent
- Excellent
- Excellent
- Very Good
- Excellent
- Very Good
- Good to Excellent
- Good

*This data is based on tests believed to be reliable and consistent with industry practices and is presented in good faith. No warranty or representation including but not limited to merchantability or of fitness for use whether expressed or implied is intended or made, nor is protection from law or patent to be inferred. All rights and patents reserved.*

**Fairprene is a registered trademark of Alpha Engineered Composites.**

**As always, made 100% in the USA...**



*\*NN-0060 is used for reference only and may be the property of others*