



FAIRPRENE® PRODUCT BULLETIN: N6C2

Product Code:

WFP-N6C2

[Comparable to NC-6088 Neoprene Coated Nylon Fabric (uncured)]*

Description:

Uncured neoprene black coated cotton fabric designed for use as water, oil and hydraulic seals and packings as well as for other general industrial purposes. This product offers improved aesthetics over basic white cotton for critical applications.

Typical Physical Properties:

Base Fabric:	Dyed Black Base Cloth	12 osy
Coating:	CR (Neoprene)	High Strength Formulation
Coated Fabric:	70 Durometer (Shore A)	ASTM D-412
Mullen Burst:	310 psi min.	ASTM D-751
Tensile Grab:	132 lbs./in.	ASTM D-751
Finish Weight:	16 osy	ASTM D-751
Finished Width:	As specified to 48"	

General Polymer Characteristics:

Neoprene / Chloroprene

Resistance To:

Aliphatic Hydrocarbons	Good
Aromatic Hydrocarbons	Fair
Oxygenated (Ketones, etc.)	Poor
Lacquer Solvents	Poor
Oil & Gasoline	Good
Animal & Vegetable Oil	Good
Water Absorption	Good
Oxidation	Excellent
Ozone	Excellent
Sunlight	Very Good
Heat Aging	Good to Excellent
Flame	Very Good
Heat	Good to Excellent
Cold	Good

This data is based on tests believed to be reliable and consistent with industry practices and is presented in good faith. No warranty or representation including but not limited to merchantability or of fitness for use whether expressed or implied is intended or made, nor is protection from law or patent to be inferred. All rights and patents reserved.

**NC-6088 is used for reference only and may be the property of others*

Fairprene is a registered trademark name of Alpha Engineered Composites



www.fairprene.com

As always, made 100% in the USA...