



N1RS

Product Code:

WFP-N1RS

[Compare to NS-5565*, Neoprene Sheet Stock]



Description:

Neoprene sheet stock material with superior quality for highly engineered applications. All Fairprene® materials are manufactured to exact standards and close tolerances.

Typical Physical Properties:

Tensile (psi):	1400 min. (1,800 typical)	ASTM D-751
Durometer:	65 Shore A	
Finish Gauge:	.016", .031", .062", .125" (Custom gauges available upon request)	
Finished Width:	48"	

General Polymer Characteristics:

Resistance To:

	<u>Neoprene (CR)</u>
Aliphatic Hydrocarbons	Good
Aromatic Hydrocarbons	Fair
Oxygenated (Ketones, etc.)	Poor
Lacquer Solvents	Poor
Oil & Gasoline	Good
Animal & Vegetable Oil	Good
Water Absorption	Good to Excellent
Oxidation	Excellent
Ozone	Excellent
Sunlight	Very Good
Heat Aging	Excellent
Flame	Very Good
Heat	Good to Excellent
Cold	Good

The information supplied herein is based upon information currently available on the subject. This data is based on tests believed to be reliable and consistent with industry practices and is presented in good faith. No warranty or representation including but not limited to merchantability or of fitness for use whether expressed or implied is intended or made, nor is protection from law or patent to be inferred. All rights and patents reserved.



TRELLEBORG

Fairprene® is a registered trade name of Trelleborg Engineered Coated Fabrics
www.TrelleborgECF.com

www.fairprene.com