



FAIRPRENE® PRODUCT BULLETIN: N6C2

Product Code:

WFP-N6C2

[Comparable to NC-6088 Neoprene Coated Nylon Fabric (uncured)]*

Description:

Uncured neoprene black coated cotton fabric designed for use as water, oil and hydraulic seals and packings as well as for other general industrial purposes. This product offers improved aesthetics over basic white cotton for critical applications.

Typical Physical Properties:

Base Fabric:	Dyed Black Base Cloth	12 osy
Coating:	CR (Neoprene)	High Strength Formulation
Coated Fabric:	70 Durometer (Shore A)	ASTM D-412
Mullen Burst:	310 psi min.	ASTM D-751
Tensile Grab:	132 lbs./in.	ASTM D-751
Finish Weight:	16 osy	ASTM D-751
Finished Width:	As specified to 48"	

General Polymer Characteristics:

Resistance To:

Aliphatic Hydrocarbons
 Aromatic Hydrocarbons
 Oxygenated (Ketones, etc.)
 Lacquer Solvents
 Oil & Gasoline
 Animal & Vegetable Oil
 Water Absorption
 Oxidation
 Ozone
 Sunlight
 Heat Aging
 Flame
 Heat
 Cold

Neoprene / Chloroprene

Good
 Fair
 Poor
 Poor
 Good
 Good
 Good
 Excellent
 Excellent
 Very Good
 Good to Excellent
 Very Good
 Good to Excellent
 Good

The information supplied herein is based upon information currently available on the subject. This data is based on tests believed to be reliable and consistent with industry practices and is presented in good faith. No warranty or representation including but not limited to merchantability or of fitness for use whether expressed or implied is intended or made, nor is protection from law or patent to be inferred. All rights and patents reserved.



TRELLEBORG

*Fairprene® is a registered trade name of Trelleborg Engineered Coated Fabrics
www.TrelleborgECF.com*

www.fairprene.com